

# tattoo

the thermal transfer card printer

The monochrome  
plastic card printer



Monochrome  
Thermal  
Transfer



300 dpi



Single-Sided



7 s/card




100 cards



0.25-0.76mm  
(10-30mil)

www.evolis.com



# tattoo

the thermal transfer card printer

Hi-Tech design, compactness and ease of use, the **Tattoo** revolutionizes the world of monochrome printing on plastic cards.

In a few seconds, the **Tattoo** personalizes your pre-printed or blank plastic cards. It prints your high resolution texts, barcodes, graphics and logos.

Representing the ideal for visitor badges, loyalty cards, subscription cards, and much more, the **Tattoo** can be integrated in all types of environment: offices, bank receptions, shop counters. The **Tattoo** is today the most compact of all plastic card printers.

A mixture of technology and innovation, the **Tattoo** offers a double loading mode: card by card manual feeding (card introduced at the front) and automatic feeding thanks to its 100 card feeder. This detachable and completely enclosed feeder makes it possible to prepare several series of cards and to guarantee an optimal printing quality.

**Tattoo, the small revolution!**



Tattoo Stand-Alone

### Print Mode

- Monochrome thermal transfer
- Line mode for printing texts, barcodes, graphics and logos or diffusion mode for photo printing

### Printer Specifications

- Integrated ribbon saver
- Automatic card thickness adjustment

### Print Speed

- 500 cards/hour

### Resolution

- 300 dpi (11.8 dots/mm)

### Windows™ Drivers

- For Windows™ 95 / 98 / Me / NT 4.0 / 2000 and Xp

### Warranty

- Printer: 1 year
- Print head: 1 year, unlimited number of prints<sup>1</sup>

### Ribbon Type

- Monochrome ribbon: 600 cards/roll
- Colors available: black, blue, red, green, gold and silver

### Card Loading Modes

- Manual and/or automatic feed

### Options

- USB port (cable supplied)
- Serial port (available upon study)
- Additional detachable card feeder

### Other printer models

Tattoo Mag	Tattoo Stand-Alone
Printer with HICO / LOCO magnetic stripe encoder - ISO 7811	Printer connected to a keyboard, available upon study

<sup>1</sup> - Clause governing the use of Evolis consumables

<b>Card types</b>	PVC, Composite PVC, ABS and card board
<b>Card format</b>	ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125") Maximum print area: 52 mm x 83 mm (2.04" x 3.26")
<b>Card thickness</b>	0.25 mm (10 mil) to 0.76 mm (30 mil)
<b>Card feeder capacity</b>	300 cards (0.25 mm - 10 mil) - 100 cards (0.76 mm - 30 mil)
<b>Resident barcodes</b>	Code 39, Code 2/5 interleaved
<b>Resident fonts</b>	Arial normal 100, Arial bold 100
<b>Printer size</b>	• Height: 166 mm (6.53") • Width: 290 mm (11.42") • Depth: 187 mm (7.36")
<b>Printer weight</b>	2,5 Kg (5.5 lbs)
<b>Communication interface</b>	Centronics Parallel (cable supplied)
<b>Electrical</b>	110-230 Volts CA, 60-50 Hertz
<b>Environmental</b>	• Min / Max operating temperatures: 15° / 30° C (59° / 86° F) • Humidity: 20% to 65% non-condensing • Min / Max storage temperatures: -5° / +70° C (23° / 158° F) • Storage humidity: 20% to 70% non-condensing • Operating ventilation: free air



www.evolis.com

Headquarters: Evolis Card Printer  
29, avenue de la Fontaine - Z.I. Angers Beaucouzé  
49070 BEAUCOUZÉ - France  
Tel: +33 (0) 241 367 606  
Fax: +33 (0) 241 367 612  
info@evolis.com - www.evolis.com

Evolis Asia / Pacific  
151 - D King's Road, #17-14  
SINGAPORE 268161 - Singapore  
Tel: +65 4745901  
Fax: +65 4765771